

LIS007521943B2

(12) United States Patent

Binder et al.

(54) DEVICE, METHOD AND SYSTEM FOR ESTIMATING THE TERMINATION TO A WIRED TRANSMISSION-LINE BASED ON DETERMINATION OF CHARACTERISTIC IMPEDANCE

(75) Inventors: Yehuda Binder, Hod Hasharon (IL);

Ami Hazani, Ra'anana (IL)

(73) Assignee: Serconet, Ltd., Ra'anana (IL)

(*) Notice: Subject to any disclaimer, the term of this

patent is extended or adjusted under 35

U.S.C. 154(b) by 751 days.

(21) Appl. No.: 11/091,371

(22) Filed: Mar. 29, 2005

(65) **Prior Publication Data**

US 2006/0176044 A1 Aug. 10, 2006

(30) Foreign Application Priority Data

(51) Int. Cl. G01R 27/08

G01R 27/00

(2006.01) (2006.01)

(52) **U.S. Cl.** **324/691**; 324/71.1

See application file for complete search history.

(56) References Cited

U.S. PATENT DOCUMENTS

5,010,399 A	4/1991	Goodman et al.
5,193,108 A	3/1993	Stocklin
5,621,455 A	4/1997	Rogers et al.
5,633,801 A *	5/1997	Bottman 324/600
5,734,658 A	3/1998	Rall et al.
5,841,360 A	11/1998	Binder
5,896,443 A	4/1999	Dichter
6,069,899 A	5/2000	Foley

(10) Patent No.: US 7,521,943 B2 (45) Date of Patent: Apr. 21, 2009

6,108,331 A 8/2000 Thompson 6,216,160 B1 4/2001 Dichter

6,396,391 B1 5/2002 Binder

(Continued)

FOREIGN PATENT DOCUMENTS

EP 0 768 537 A1 4/1997

(Continued)

OTHER PUBLICATIONS

Fowler, Bill, "Transmission Line Characteristics", National Semiconductor Application Note 108, National Semiconductor Corporation, Jul. 1986, pp. 1-8.

(Continued)

Primary Examiner—Timothy J Dole (74) Attorney, Agent, or Firm—Browdy and Neimark, P.L.L.C.

(57) ABSTRACT

A system and method for measuring a characteristic impedance of a transmission-line comprises transmitting energy to the line, and shortly after measuring the voltage/current involved and thus measuring the equivalent impedance. The measured characteristic impedance may then be used in order to determine the termination value required to minimize reflections. In another embodiment, the proper termination is set or measured by adjusting the termination value to achieve maximum power dissipation in the terminating device. The equivalent characteristic impedance measurement may be used to count the number of metallic conductors connected to a single connection point. This abstract is not intended to limit or construe the scope of the claims.

26 Claims, 17 Drawing Sheets

